

# SNIP WOODLAC SANDING SEALER



## Product detail

Woodlac Sanding Sealer is a Nitrocellulose based fast drying high quality sealer. It has versatile sanding properties which give good filling, leveling and smooth surface for Lacquer and Melamine.

Application Process:-

Application	Thinner	Dilution % (by volume)	Recoat Gap Time
Step 1 Apply first coat of Woodlac Sanding Sealer and sand the surface with sand paper no. 320 or 400.	Woodlac Melamine Thinner	1:2	2 – 3 Hrs.
Step 2 Apply second coat of Woodlac Melamine Sealer and sand the surface with sand paper no. 320 or 400.	Woodlac Melamine Thinner	1:2	5 – 6 Hrs.

Note:- Woodlac Melamine can be applied with Brush or conventional Method.

Pack Size :- 20 Ltr, 4 Ltr and 1 Ltr Pack Size  
 Coverage :- 90-100 sqft  
 Finish :- Matt finish.  
 Method of Application :- Brush, Airless spray

THINNING :- Thin one part of Woodlac Sanding Sealer with two parts of Woodlac Thinner.

## PRECAUTIONS

- Do not mix above recommended ratios.
- Stir well and strain before use.
- Keep away from direct heat
- Avoid Eye and skin contact.

## Advantages:-

- Lead Free
- Low VOC
- Eco Friendly
- High Performance
- Outstanding coverage and Economical
- Long term protection against daily wear and tear

## Surface Preparation:-

All the surfaces should be thoroughly dry, clean and free from oil. Sand the wooden surface along the grains with sand paper no.180 then 320 or 400 and clean the surface with cloth, if surface has dent apply Woodlac Wood filler with a putty tool over the affected area. To get the desired shade use Woodlac wood stainer with Woodlac melamine. Mix the base and hardner in the ratio 9:1 by volume. Thin final product with Wodlac Melamine thinner and allow 30 minutes to the mixture to get ready to use. Apply 2 coats of woodlac Melamine sealer followed by 2 coats of Woodlac Melamine Glossy or Matt finish.

# Woodlac Sanding Sealer